

1				2			3	4		5		6		7		8	
Rating Data UL/CSA maximum Horse- power rating (HP) 50/60 Hz				AC 4 Inching and Plugging 30,000 Operations			General use con- tinuous current open (90% if enclosed)	Standard auxiliary contacts		AC Operated non-reversing		DC Operated non-reversing					
3 phase				3 phase				Amps	NO	NC	Type	Price	Type	Price			
											Important: Add coil voltage and frequency from page 3/46 - 3/47 to end of type. See below for more details.		Important: Add coil voltage from page 3/46 - 3/47 to end of type. See below for more details.				
200 V HP	230 V HP	460 V HP	575 V HP	230 V HP	460 V HP	575 V HP					\$			\$			
30	30	60	75	20	40	50	120	2	2	DIL 3-22	See Price List	See Price List	DIL 3-22/G	See Price List	See Price List		
40	50	100	100	25	50	60	160	2	2	DIL 4-22	See Price List	See Price List	DIL 4-22/G	See Price List	See Price List		
60	75	150	175	50	100	125	210	2	2	DIL 6-22	See Price List	See Price List	DIL 6-22/G	See Price List	See Price List		
75	100	200	250	60	125	150	360	2	2	DIL 8-22	See Price List	See Price List	DIL 8-22/G	See Price List	See Price List		
125	150	300	350	-	-	-	400	2	2	DIL 8A-22	See Price List	See Price List	DIL 8A-22/G	See Price List	See Price List		

Magnetic Contactors
Magnetic Starters

3

Additional Information	Page
Technical Data	3/50
Dimensions	3/61
Overload Relays	4/2
Accessories	3/35

Stock Coil Voltages	
24 V 60 Hz	120 V DC
120 V 60 Hz / 110 V 50 Hz	
208 V 60 Hz	
240 V 60 Hz / 220 V 50 Hz	
See page 3/46 for other available coil voltages. Some DC coils may require use of a DC interposing relay.	

General

Moeller Electric's DIL "Universal" contactors can provide a cost-effective solution for motor switching in applications that do not require the full modularity of DIL...M contactors. They are UL listed and CSA certified and in compliance with IEC/EN 60 947 standards. Universal Contactors are also CE marked. 2NO and 2NC auxiliary contacts are provided standard for each contactor. Each auxiliary contact can be reversed to achieve 3NO + 1NC, 1NO + 3NC or 4NC contact configurations. Optional NO-early make and NC-late break contacts are also available.

How to Order

To Order Specify:	Example:
1 Type Number	100 HP @ 460 V AC (column 1), 3 PH contactor,
2 Coil Voltage	2NO and 2NC auxiliary contacts and 120 V 60 Hz coil
	Type Number Coil Voltage
	DIL 4-22 120 V 60 Hz